



AVer CAM130 **Brighter and Better Meetings** 4K Camera with Intelligent Lighting for Small Rooms and WFH



Camera

- 120° FOV, up to 5X zoom via ePTZ*
- OSony 4K sensor: ultra-crystal-clear image in any lighting
- Trame rates: (16:9) 4K 30fps; 1920 x 1080, 1600 x 900, 1280 x 720, 960 x 540, 848 x 480, 800 x 448, 640 x 360, at 60, 30, 15fps; (4:3) 1280 x 960, 800 x 600, 640 x 480 at 60, 30, 15fps
- Intelligent fill light: automatically adjusts lighting levels to make you look energetic in a dim environment**
- O Supports autofocus: SmartFrame function automatically adjusts the FOV to track and fit all participants on screen
- OInnovative Preset Framing: follows the presenter through preset areas
- True WDR up to 120db: 3D noise-reduction and superb backlight compensation optimize lighting in high-contrast conditions
- Mirror, flip, AE, white balance: auto/manual override via PTZApp 2
 Minimum focus distance: 60 cm
- ⑦People-counting API: enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
- 10 camera presets (through remote control and IP web page)
- Standard tripod screw holes
- *Please use PTZApp 2 to set up 5X zoom.

**For best lighting results, sit within 1 meter away from the camera.

Microphone

D microphones
Frequency response: 100–12K Hz
Sensitivity: -37 dB
Echo cancellation and background noise suppression

Connectivity

 ③USB type-C 3.1 connector, backward compatible with USB 2.0
 ③DC jack for power adapter (for USB 2.0 connection while using filllight function)

Video Format

YUV, YUY2, MJPEGH.264 (UVC 1.5)

USB

③3.1 Gen 1, backward compatible with USB 2.0
 ④UVC 1.1 (USB video), UAC 1.0 (USB audio), UVC1.5*

*UVC1.5 requires an additional firmware upgrade. Please contact technical support for more details.

Control

IR remote control
UVC/UVA plug-and-play
PTZApp 2

Security and Mount

Built-in TV clip
Kensington slot
1/4" tripod mounting screw

System Requirements

Windows ® 7/10/11
 Mac OS X 14.4 or later
 Google Chromebox 3 version 94.0.4606.114 or later

Hardware Specs

③3.2 GHz Intel[®] Core[™] i5-4460 processor
④4 GB RAM or more
④USB 3.1 port, backward compatible with USB 2.0

Power Supply

⑦AC 100V−240V, 50/60 Hz
⑦5V/2A

Free Applications for Meeting Collaboration (For Windows® and Mac® computers)

EZManager 2: Camera Central Management Software ③Remotely group FW/SW upgrades, control the camera, and manage settings

PTZApp 2: Camera Settings Software

- View live video, people-counting numbers, and meetinginterval information
 Enable Skype for Business far-end control
- Certable Skype for Busiliess far-end contro
- OUpgrade firmware automatically or manually
- Ocontrol the cameraSet parameters and adjust the camera image
- [®]Diagnose operating status

EZLive: Broadcasting Software

③Enjoy multi-camera real-time streaming, annotating, image capturing, and video recording

Environmental Data

Operation temperature: 0 to 40°C
Operation humidity: 20% to 80%
Storage temperature: -20 to 60°C
Storage humidity: 20% to 80%

Dimensions

Package dimensions: 217(L)*155(W)*118(H) mm
 Package weight: 0.729 kg
 Camera: 160 (L) x 37 (H) x 60 (D) mm/ 0.282kg
 Remote control: 149.72 x 42.3 x 19.29 mm/50g (optional item)

Package Contents

OCAM130 unit
Power adapter (10 ft/3 m)
USB 3.1 type-C to type-A cable (6 ft/1.8 m)
QR code card
Tripod screw

Optional Accessories

Remote control (also compatible with VB130)
USB 2.0 type-C to type-A cable (15 ft/5 m)
USB 3.1 Extension Cable (10 m/20 m/30 m)

Warranty

Camera: 3 years*
Accessories: 1 year
*We offer an optional 2-year extended warranty in Europe. Please contact your local supplier for details.

Compatible Applications

Zoom, Microsoft® Teams, Skype, Skype for Business, Google Meet, RingCentral, BlueJeans, Intel® Unite™, Fuze, Adobe® Connect™, CyberLink U Meeting®, Cisco WebEx® GoToMeeting™, LiveOn, Microsoft® Lync™, TrueConf, V-Cube, Vidyo, vMix, WebRTC, Wirecast, XSplit

*For 4K UHD support, please check system/hardware requirements with your software application provider.

**Specifications may vary depending on countries and are subject to change without notice.

Product Overview



Side







Tripod screw hole



 $\$ 2023 AVer Information Inc. All rights reserved. All brand names and logos are trademarks of their respective companies.

www.aver.com