



## AVer CP10 Collaboration Controller

# Safe and Easy Collaborative Touch Easy Access to Video Conferencing Solutions



### **Product Specifications**

#### **Display**

- · Antibacterial glass panel\*
- 10.1-inch anti-fingerprint screen
- · Resolution: 1280 x 800
- · Aspect ratio: 16:10
- Comfortable and ergonomic viewing angle:
   Built-in table stand with a 23° display angle
   Optional wall mount with a 68° display angle

\*Antimicrobial glass is FDA (USA) &SIAA (JP) certified.

\*Unlike normal antimicrobial film or spray, CP10's glass uses ion exchange technology to maintain antibacterial effectiveness for the product's lifetime.

#### **Technology**

- · Capacitive-touch sensor supports 10 touch points
- Side LED bar clearly reveals meeting status: Muted/unmuted/room availability\*
- A single RJ45 cable carries both data and power to keep the table neat
- · G-sensor for screen rotation

#### **System**

· Android 10

#### **Mount and Security**

- · Wall-mount kit (optional)
- · Kensington security lock

#### **Connectivity**

- Power over Ethernet (PoE+)
- USB 2.0 Type A (x1) for diagnostics and firmware upgrades

#### **Power**

· Consumption: 12V/1A

#### **Product Overview**

#### Front



#### **Back**



#### **Applications for Meeting Collaboration**

- · Zoom Rooms controller app (preinstalled)
- · AVer PTZApp2: Camera setting software (preinstalled)\*
- · View live video, set camera parameters
- · Intuitive touch interface for camera control
- · Compatible with AVer USB cameras
- \*1. The PTZApp2 on the CP10 is different from the PC version.
  \*2. The PTZApp2 on the CP10 will first support CAM520 Pro, CAM520 Pro2,

VC520 Pro, VC520 Pro2, and VB130 via Ethernet connection. Support for these and other Aver USBCAMs via USB connection to PC will be available in August 2021.

#### **Package Contents**

- · CP10
- · Quick Start Guide
- · Warranty statement

#### **Optional Accessories**

- 1-port POE+ injector, compatible with 802.3 at or af standard
- · Wall mount

#### **Environmental Data**

- Operation temperature: 0 to 40°C
- · Operation humidity: 20% to 80%
- Storage temperature: -20 to 60°C
- · Storage humidity: 20% to 80%

#### **Dimensions**

- Package dimensions: 328 (L)x 215 (W)x 125 (H)mm
- · Package weight: 1kg / 2.2lbs
- · CP10 unit: 250 mm x 174 mm x 85 mm / 0.9 kg

#### **Warranty**

- . 2 years parts and labor warranty
- \*Specifications may vary depending on countries and are subject to change without notice.

#### Slide-in mount







<sup>\*\*</sup>Bright and black dot in the LCD panel: maximum 3 dots for each.