

# AVer EVC130

## Full HD Video Conferencing Endpoint



### Package contents

- Main system unit (codec)
- EVC eCam PTZ camera
- EVC microphone array
- IR remote control with batteries
- Power supply
- Cables
- Warranty card
- Quick guide

### Communications

- H.323, SIP standards, SIP TLS
- Bandwidth from 64Kbps to 4Mbps (H.323/SIP)
- Minimum bandwidth 64Kbps (audio+video)
- Manual bandwidth selection (64, 128, 192, 256, 384, 512, 768, 1024, 1152, 1472, 1536, 1920, 2048, 3072, 4096 Kbps)
- RJ45 network LAN (10/100/1000)

### Camera

#### EVC eCam Focus camera

- 2-megapixel CMOS sensor
- 4X digital zoom
- ±100° pan; ±25° tilt
- 88° FOV (D), 77° FOV (H)
- Operated by remote controller or remote application.
- Supports FAR/NEAR camera control

### People video resolutions

- HD1080p (1920 x 1080)
- HD720p (1280 x 720)
- 480p (848 x 480)
- 4CIF (704 x 576)
- 4SIF (704 x 480)
- 360p (640 x 360)
- W288p (512 x 288)
- CIF (352 x 288)
- SIF (352 x 240)
- All resolutions at 30fps

### Content video resolutions

#### Supported resolutions:

- WSXGA (1440 x 900)
- HD (1360 x 768)
- SXGA (1280 x 1024)
- SXGA (1280 x 960)
- WXGA (1280 x 800)
- XGA (1024 x 768)
- SVGA (800 x 600)
- VGA (640 x 480)

### Output resolutions:

- HD720p (1280 x 720) up to 30fps

### Video standards

- H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261
- H.239 dual video streams
- BFCP content sharing

### Video feature

- Upside-down (camera invert), White balance

### Video inputs

- EVC eCam PTZ camera
- VGA

### Audio standards

- G.711, G.722, G.722.1, G.728, G.722.1C

### Audio features

- Automatic gain control (AGC)
- Advanced noise reduction (NR)
- Acoustic echo cancellation (AEC)

### Audio inputs

- EVC microphone daisy chain up to 4 mics (with cable)
- Line-in (3.5 mm)

### Audio outputs

- HDMI
- Line-out (3.5 mm)

### Other supported standards

- H.224, H.225, H.245, H.281, H.323 Annex Q, H.460
- SRTP, H.235, HTTP, HTTPs, Telnet, DHCP, DNS

### User interface

- Multiple layout styles
- Single/dual monitor layout styles
- User-friendly OSD (23 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish, Vietnamese)
- Display/edit site name

### Network

- 10/100/1000Mbps
- NAT / firewall traversal (H.460)
- High Efficiency Lost Packet Recovery (HELPeR)
- Packet Loss Recovery (PLR)
- API support via Telnet
- Wake-on-LAN (WOL) support



- IPv4 and IPv6 support
- Quality of Service (QoS)
- Network test
- VLAN (802.1Q / 802.1P),
- EAP 802.1x

### Security

- AES (Advanced Encryption Standard) function (128-bit) and H.235
- Password protection for system settings
- Password protection for remote system management

### Web management tool

- Remote management through the Web
- Live monitoring via the Web
- Firmware update via Ethernet / Internet
- Phonebook download / upload / edit
- Restore system settings
- Export call history
- HTTP and HTTPS

### Value-added features

- Meeting recording
  - In meeting and offline recording
  - Save directly to USB flash drive
  - Supports screen re-layout during playback
  - Playback and file conversion via VCPlayer software (.mov and .mp4 format)
- Dual monitor support output (people video and content sharing)
- Speed dialing via hot keys (10 sets)
- Camera presets (100 positions)
- Network Time Protocol (NTP)
- Firmware update via USB flash driver
- Screensaver and auto power off mode
- Telnet access for management (control API)
- ScreenShare software (PC and MAC content sharing via wifi/network infrastructure)

- VLink software (APP for remote management and sharing)
- LDAP directory
- Supports SIP voice calls
- SnapShot save
- iSCSI storage device settings

### Power supply

- AC 100V~240V, 50/60Hz
- Consumption: EIAJ 12V, 5A

### Environmental Data

- Operation temperature: 0~40°C
- Operation humidity: 20%~80%
- Storage temperature: -20~60°C
- Storage humidity: 20%~80%

### Physical characteristics

- Package dimensions: 330 x 230 x 265 mm
- Package weight: 3.7kg
- Main system (codec): 260 x 158.7 x 33 mm
- eCam Focus camera: 137.7 x 122.3 x 130 mm
- EVC microphone array: 131.9 x 118.6 x 25.5 mm

### Optional accessories

- Additional microphone
- Camera mount
- Replacement eCam PTZ camera
- USB-to-RS232 converter

### Warranty

- 3+2 year warranty\*

\* Please register online to receive free 2 year warranty extension. For detailed warranty information, please contact an AVer representative.

## eCam Focus Camera



## Hardware specifications

### Front panel



### Back panel



## Software Add-ons

### VCLink

**Video Conferencing Control and Sharing for your smartphone.**

VCLink is a free app that transforms your mobile device into a fully functional remote control for your AVer Video Conference solution. Initiate a call, share content, pan, tilt, zoom, control far systems, set meetings to record, take snapshots and more right from your smart phone from anywhere in the world your service allows. Find "VCLink" from Apple or Android app store.



### ScreenShare

**Video Conferencing wirelessly share content**

ScreenShare is a free download for Windows and Mac, AVer ScreenShare allows users to wirelessly share content from their laptop directly into a live meeting without having to connect a VGA cable. Presentations, images, videos and more can be shared to the meeting from anywhere in the room. Download "ScreenShare" from AVer's add-on software download center.



### VCPlayer

**Easily playback on PCs and notebooks, and convert files to .mp4 and .mov**

View and manipulate recorded conferences of this specially designed video playback software. Watch video files recorded using AVer's exclusive one-touch recording feature and even change the layout during playback to catch details you might have otherwise missed. If you need to view the video using another media player, just convert the video from its original format to the more widely used .mov format.



### WebTool

**Manage the system via any browsers**

With WebTool, select staff can use the Internet to access their AVer video conferencing systems. WebTool's camera control feature gives technical support staff the means to remotely access the camera / codec, and monitor what's happening in the call, to troubleshoot issues as quick and effectively as if they were in the meeting room. WebTool's remote monitoring feature supports video only.

