Product Specifications

- · Sony super-low-light 2M pixel sensor for clear and natural imaging in low-light conditions
- Resolution: (16:9) 1920 x 1080, 1600 x 900, 1280 x 720, 960 x 540, 848 x 480, 800 x 448, 640 x 360, 424 x 240, 320 x 180; (4:3) 800 x 600, 640 x 480, 480 x 360, 320 x 240
- SmartFrame for automatic FOV adjustment to fit all
- · Smart Gallery* function offers great visibility for individual participant in the meeting room
 Innovative Preset Framing: Follow presenter based on
- True WDR up to 120dB: Superb backlight compensation technology for optimizing light balance in high-contrast
- Zoom: 24X* total zoom (12X optical zoom)
- Field of view(D/H/V): 84.5°/76°/48° · Lens focal length: 3.9 mm (wide) ~ 47.3 mm (tele)
- Lens F#: 1.8 (wide) ~ 2.8 (tele)
- Mirror, Flip, AE, white balance: auto, manual override via
- · Minimum focus distance: 1.5 m Standard tripod screw holes and Kensington slot
- People-counting API: enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage

Speakerphone

- · Full duplex microphone array with echo cancellation
- · Advanced noise suppression
- · Dual-omnidirectional microphone array
- · 3.5 mm line out
- Speaker: 6W, Adjustable to 90dB SPL at 0.5 m
- Touch controls for volume down/up, mute, phone input (Microsoft Teams SKU w/o this function), call, hang-up, and. Teams button*
- Bridge phone-in and USB into one call

- · Remote side: VISCA over IP, IP (RJ45)
- UVC/UAC plug-and-play
 WebUI: Browser IP access via Chrome (does not support
- Internet Explorer)
- PTZApp 2

Video Format

- Network video compression format: H.264, H.265
 Network protocols: RTSP, RTMP

Motorized Pan & Tilt Movement

- Tilt: +90° (up) -30° (down)
- · 10 camera presets (via remote control) · Fast and quiet pan & tilt movement

- · Mini DIN9 for RS232 in & out connection (VISCA control panel and camera daisy-chain)
- · USB 3.1 Type-B connector

- · 3.1 Gen 1 Type-B, backward compatible with USB 2.0
- · UVC 1.1 (USB video), UAC 1.0 (USB audio), UVC1.5*

Mount

- · Camera wall-mount bracket included

System Requirements

- · Mac OS X 14.4 or later · Google Chromebox 3 version 94.0.4606.114 or later

Hardware Specs

- · 3.2 GHz Intel® Core™ i5-4460 Processor or higher
- · 4 GB RAM or more USB 3.1 port, backward compatible with USB 2.0 port

Environmental Data

- \cdot Operation temperature: 0°C \sim 40°C
- Operation humidity: 20% ~ 80%
- · Storage temperature: -20°C ~ 60°C
- · Storage humidity: 20% ~ 80%

Dimensions

- · Package dimensions: 259 x 259 x 349 mm*
- Package weight: 5.4 kg*
- · Camera: 142.7 x 153 x 182 mm/1.45 kg
- Speakerphone: 220 x 181.5 x 49.5 mm/0.85 kg Remote control: 200 x 50 x 21 mm/0.09 kg

Optional Accessories

- · Expansion Speakerphone · Expansion Microphone
- · Foldable TV mount
- · USB3.1 fiber extender 10m/20m/30m
- · USB3.1 type-B to type-A cable 3m

Web page browser requirement

- Firefox: version 69 or above · IE: Not support

Power Supply

- \cdot AC 100V \sim 240V, 50/60 Hz
- · Consumption: 12V, 5A

Free Applications for Meeting Collaboration (Windows® and Mac)

EZManager 2: Camera Central Management software

Remotely group FW/SW upgrades, control the camera, and configure settings

- Smart Gallery/ Virtual USB streaming/ Preset Link
- Upgrade firmware automatically or manually
- · Set parameters and adjust camera image
- Diagnose operating status View live video

· Real-time streaming / annotating / snapshots / video recording

Package Contents

- VC520 Pro2 Speakerphone
- Remote control Power adapter
- Power cord (6 ft/1.8 m)
- USB2.0 type-B to type-A cable (16.5 ft/5 m)
 Camera to Speakerphone Cable (33ft/10m)
- 3.5 mm aux cable (3 ft/0.9 m)

- ¼" tripod screw
- · 2 Expansion Microphone and 5 m Cable*

Warranty

- · Camera / Speakerphone: 3 years*
- · Accessories: 1 year

Compatible Applications

Zoom, Microsoft® Teams, Skype for Business, Skype, Google Meet, Intel® Unite™, RingCentral, BlueJeans V-Cube, LiveOn, CyberLink U Meeting®, TrueConf, Vidyo, Adobe® Connect™, Cisco Webex®, Fuze, GoToMeeting™ Microsoft® Lync™, vMix, WebRTC, Wirecast, XSplit

Audio Format

- · Network protocol: RTSP, RTMP

Hardware Specifications

CAMERA BACK PANEL



RS232 in/out

Available with VC520 Pro2 Speakerphone set

USB 3.1 Type-B DC 12V

SPEAKERPHONE BACK PANEL

Daisy-chain up to



3 speakerphones or 4 microphones

SPEAKERPHONE



Standard edition



Microsoft Teams edition



©2022 AVer Information Inc. All rights reserved. All brand names and logos are trademarks of their respective companies. Distributor/Dealer



AVer











VC520 Pro2

Professional Conferencing System

for Mid-to-Large Rooms




(EFC RoHS www.aver.com 202205

Smart Presenting With A Lifelike Audiovisual Experience

The VC520 Pro2 is an expert-level conferencing system. Equipped with an 24X* total zoom, advanced AVer SmartFrame, IP video streaming, single USB installation, and an extended speakerphone solution, the VC520 Pro2 brings you an extraordinary video conferencing experience.











Every Detail



Improved

Speakerphone

Get Perfect Audio with an Extended Speakerphone

The VC520 Pro2 offers balanced and steady audio performance. As the first conferencing system in the industry to deliver a daisy-chain function, the VC520 Pro2 supports either up to two expansion speakerphones or a full duplex microphone array. The inventive speakerphone makes the VC520 Pro2 a flexible option for fit mid-to-large conference rooms.

Support Video and Audio with One USB Cable

Installing the VC520 Pro2 is super easy. All you need to get set up for a call is a single USB cable. This direct connection not only saves time but also keeps your meeting table tidy and organized. Simplify your setup process and decrease installation costs with the VC520 Pro2.

Spot Every Detail with an 24X* **Total Zoom**

Present products in extreme clarity and demonstrate every detail with an 24X* total zoom. The VC520 Pro2 also maximizes team collaboration with smoother video imaging than ever at up to 1080p, 60fps quality.

* Please use PTZApp 2 to set up 24X zoom.

Improve Meeting Safety & Efficiency with SmartFrame

AVer developed an advanced SmartFrame function that conforms to the latest trends. Equipped with this upgraded auto-framing feature, the VC520 Pro2 can detect and frame meeting participants even when they wear masks or present facial profiles from up to 7 meters away. The VC520 Pro2 cuts through triviality and greatly improves conferencing efficiency.

VC520 Pro2 Microsoft Teams **Rooms Edition**


This exclusive version of the VC520 Pro2 speakerphone lets you start meetings instantly with an embedded Microsoft Teams button* and LED status indicator. Just touch the button to enter a meeting and check the call status. Also, you can enjoy an always-clear audio experience via the two expansion microphones that come with this special edition system.

*Only available for the VC520 Pro2 Microsoft Teams edition, which includes a camera, a speakerphone, and two expansion microphones













One USB Cable



Safety & Efficiency Extension Solutions

