EXPAND Vision 5 Series

Take video conferencing to a new level with EXPAND Vision 5 for small and medium-sized meeting rooms. A powerful all-in-one video bar with razor-sharp video and outstanding audio performance thanks to two integrated speakers and four microphones.



red

t winner 2023







Supports USB mode

Key Features

All-in-one product

Speakers, camera, microphones, and compute are built in to make this an all-in-one device for small and medium-sized meeting rooms. No PC needed, with UC apps such as Microsoft Teams - running natively on the device

Superb audio performance

Powerful speakers carry every word clearly. Beamforming microphone array ensures crisp voice pickup and effective noise and echo cancellation

Intelligent camera solution

Wide angle 4K camera with Sony sensor and electromechanical pan/tilt for optimal room coverage. Intelligent picture framing dynamically adjusts to include all people in the room – powered by EPOS AI[™] Direct USB connection to PC or Mac[®] allows participants to bring their own device (BYOD) and run any UC solution from their laptop

Certified solution

Certified for meeting room solutions including Microsoft Teams Rooms on Android™ (with EXPAND Control) and Zoom Rooms

Fact Sheet

What's in the Box



Additional benefits & features



Easy setup and installation

Quick and effortless configuration with flexible mounting options. Use the included wall-mount to hang it above or below the display or place it directly on a table



Cable management

Integrated cable management for a tidy meeting room and a consistent set-up. Supports Kensington lock to ensure the video bar remains where it should

Enterprise-grade security Developed to meet the highest security standards



Guaranteed privacy

Comes with dedicated hard-wired mute buttons for camera and microphones



Content sharing

Share meeting content easily, through cable or wirelessly



Dual screen support

Display video content on two screens. See the presentation on one, participants on the other

Stay in control

Control the meeting with the EXPAND Control tablet or via a smart display touch screen



Centralized device management

Remote device administration and provisioning through EPOS Manager or UC provider solutions



Warranty and support

A two-year warranty ensures your investment is protected. Plus, access to EPOS Support team for questions and assistance



Automatic power saving

Goes into power saving mode when the motion sensor detects no activity in the meeting room



Statement Scandinavian design Premium materials meet Scandinavian simplicity

Black	
2,500 g / 88,2 oz	
74 x 620 x 115 mm / 2,9 x 24,4 x 4,5 in (H x L x W)	
2 years. Extended warranty available for purchase	
Android™ 10 (or later)	
32 GB	
800 Series Processor (8 Core Kryo)	
 Adreno™ 540 graphics	
Qualcomm APQ8098	
4 GB	
Up to 36 W	

2/5

Video/Camera	
Camera	4K wide-angle with Sony® sensor
Lens type	6 element aspherical low distortion lens
- Video resolution	Up to 1080p (Full HD) @ 60fps
Zoom	4x digital
Pan-tilt-zoom (PTZ)	Enhanced PTZ, Electromechanical pan/tilt ± 20°
Field of view (FOV)	100° (Horizontal) / 80° (Vertical) / 112° (Diagonal)
Depth of Field	Fixed, with a focus range from 1 - 6 m / 3,3 - 19,8 ft
Intelligent picture framing	EPOS Al™ powered
Audio	
Microphone	4 Digital MEMS enhanced beamforming microphones. Noise and echo cancelling
Microphone coverage	180° horizontal pick-up pattern
- Effective microphone range	6 m / 19 ft

Speaker

Speaker frequency response

Microphone frequency response

2 speaker drivers in suspended anti-vibration cabinets

100 - 20,000 Hz

150 - 7,500 Hz

3/5

Network & Connectivity	
Input/Output	Ethernet, HDMI in/out, USB-C, MicroSD
Ethernet	IPv4 & IPv6, DHCP/Static IP
Wi-Fi	Dual-band: (2,4/5 GHz) Standard: 802.11 ac / 802.11 ac
Bluetooth®	Version 5.0 Bluetooth® profiles: A2DP, HSP, AVRCP Microsoft Teams proximity join
Wireless sharing technology	Miracast [®]
USB mode support	Yes
Dual-screen support	Yes
Touch-screen support	Yes
Privacy/Security:	
Hardwired privacy switches	Camera / Microphone
Security lock support	 Kensington™

Crypto Engine v5, DRBG/PRNG (FIPS-compliant), Inline Cypto Engine

Encryption

Products variants	What's in the box	
EXPAND Vision 5	EPOS EXPAND Vision 5 video bar, Universal power supply, HDMI cable, Wall mount bracket, Safety guide, Quick quide and Compliance sheet	
EXPAND Vision 5 Bundle	EXPAND Vision 5: EPOS EXPAND Vision 5 video bar, Universal power supply, HDMI cable, Wall mount bracket, Safety guide, Quick quide and Compliance sheet	
	EXPAND Control: EPOS EXPAND Control, Power over Ethernet (PoE) cable, Tabletop bottom plate, Safety guide, Quick quide and Compliance sheet.	
Software		
EPOS devices can be managed with following Software solutions:		
EPOS Manager	Manage, update and configure EPOS audio and video devices from any location. For both cloud and on-premises solutions: eposaudio.com/software-epos-manager	

Product	Certifications	EAN code	UPC code 8 40064 40226 2	
EXPAND Vision 5 Art. no. 1000425	Certified for leading UC solutions incl. Microsoft Teams Rooms on Android™ (with EXPAND Control) and Zoom Rooms	57 14708 00226 0		
EXPAND Vision 5 Bundle Art. no. 1001181	Certified for leading UC solutions incl. Microsoft Teams Rooms on Android™ and Zoom Rooms	57 14708 00985 6	8 40064 40985 8	

Spare parts

Product	Art. no.	Description	EAN code	UPC code
PS - Uni O3	1001151	Power supply for EXPAND Vision 5	57 14708 00953 5	8 40064 40953 7
WM 01	1001154	Wall mount bracket for EXPAND Vision 5	57 14708 00956 6	8 40064 40956 8

Accessories

1/1

Product	Price	Art. no.	Description	EAN code	UPC code
Vision 5 - TTM 01	MSRP: €199 / \$219	1001093	Tabletop mount for EXPAND Vision 5	57 14708 00895 8	8 40064 40895 0
VISION - RC O1T		1000930	Remote control with Microsoft Teams button for EXPAND Vision 5	57 14708 00731 9	8 40064 407311





Vision 5 - TTM 01

VISION - RC 01T

Appendix

1/1

Technical	
USB output	5 V, 500 mA
Operating temperature (Max)	
Operating temperature (Min)	4 °C / 39 °F
Operating humidity (Max)	90%
Storage temperature (Min) 2 °C / 35 °F	2 °C / 35 °F
Storage temperature (Max) 45 °C / 113 °F	45 °C / 113 °F
Video (Comoro	

Video/Camera

Video standards and protocols

Encode: H.264, VP8, HEVC, MPEG-4 Decode: H.264, VP8, HEVC 8/10-bit, VP9, MPEG-4