Cisco Microphones



2

Contents

03	Product overview
04	Features and benefits
06	Product sustainability
07	Warranty information
07	Ordering information
09	Cisco Service and Support
06	Cisco Capital



Product overview

Cisco microphones provide a range of audio coverage solutions for both integrated video systems and custom video deployments – either on the table or discreetly through the ceiling (Figures 1 through 3). The microphones are optimized for voice and designed for use in small-to-large collaboration meeting rooms and specialized spaces with state-of-the-art audio quality.

Figure 1. Cisco Table Microphone



Figure 2. Cisco Ceiling Microphone



Figure 3. Cisco Microphone Array



Features and benefits

The Cisco® microphone portfolio is made up of the Table Microphone, Ceiling Microphone, and the Microphone Array.

- The Cisco Table Microphone is the latest generation microphone product for Cisco video conferencing room systems. It covers all the use cases previously served by the Table Microphone 20 and Table Microphone 60 and is ideal for omnidirectional coverage for small-to-large rooms with fixed tables. Cisco Table Microphone is available in two versions, either with a mini jack or a Euroblock plug. It is also designed to keep tables tidy and clean, as it can be recessed into the table or simply rest on a magnetic table plate.
- The Ceiling Microphone is a high-quality, costeffective directional microphone designed to cover larger meeting spaces, such as training rooms, demo rooms, and auditoriums, with discreet and easy ceiling mounting, while freeing up table space.
- The Cisco Microphone Array is a premium directional microphone array designed to provide the Cisco Webex® Room Panorama immersive video collaboration system with crystal-clear, spatial audio. It can capture participant voices from different directions and deliver multiple streams of highfidelity audio. The Microphone Array recognizes which side of the table the speaker is on. To the far-end participants, it provides a more immersive, natural experience as voices coming from the left of the table are played back remotely from the left speaker, and vice versa. It supports immersive and inclusive executive meeting and conferencing scenarios for in-person and remote participants alike-just as if they were all in the same room. Better still, the Microphone Array supports an IP-based AV setup, allowing for enhanced flexibility and lower deployment costs.

Table 1 outlines the specifications of the Cisco microphones.

Table 1. Product specifications

PRODUCT NAME	TABLE MICROPHONE	CEILING MICROPHONE	CISCO MICROPHONE ARRAY
Description	Balanced omnidirectional table microphone, boundary layer type	Balanced directional microphone (180-degree pickup pattern), boundary layer type	Digital and directional microphone array Up to 4 independent channels
Product compatibility	 Room Kit, Room Kit Plus, Room Kit Pro Room 55, Room 55 Dual, Room 70, Room 70 G2 SX10, SX20, SX80 MX700, MX800 	 Room Kit, Room Kit Plus, Room Kit Pro Room 55, Room 55 Dual, Room 70, Room 70 G2 SX10, SX20, SX80 MX200, MX300, MX700, MX800 	Room PanoramaRoom 70 PanoramaRoom 70 Panorama Upgrade
Connector	Choose between 4-pin mini jack and 4-pin Euroblock versions	Delivered with both 4-pin Euroblock and 4-pin mini jack connectors	Ethernet RJ45
Frequency range	80 Hz to 20 kHz, +/-6 dB	80 Hz to 20 kHz, +/- 6 dB	100 Hz to 16 kHz, +/- 6 dB (on axis)
Free field sensitivity	-34 dB +/- 3 dB rel 1V/Pa, 1kHz	-33 dB +/- 3 dB rel 1V/Pa, 1kHz	-22 dBFS +/- 3 dB rel 1V/Pa, 1kHz
Signal-to-noise ratio	Minimum 70 dB	Minimum 72 dB	Minimum 70 dB
Mute functionality	LED showing mute status Mute/unmute button	LED showing mute status	LED showing mute status Mute/unmute button

Table 1. Product specifications

PRODUCT NAME	TABLE MICROPHONE	CEILING MICROPHONE	CISCO MICROPHONE ARRAY
Physical dimensions (L x D x H)	Round shape 6.39 cm (diameter) x	75 x 55 x 27 cm 29.5 x 21.6 x 9.8 in	Diameter: 10 cm (3,94 inches)
	1.09 cm		Height: 3 cm (1,18 inch)
	2.52 in (diameter) x 0.43 in		10 x 10 x 3 cm
			3.94 x 3.94 x 1.18 in
			Attached cable length: 11 m (36 feet)
Weight	0.28 lb (0.126 kg)	4.08 lb / 1.85 kg	0.29 lb / 0.3 kg
Phantom power	9V/52V	12V / 48V	Power over Ethernet

Product sustainability

Information about Cisco's Environmental, Social and Governance (ESG) initiatives and performance is provided in Cisco's CSR and sustainability reporting.

 Table 2. Cisco environmental sustainability information

SUSTAINABILITY TOPIC		REFERENCE
General	Information on product-material-content laws and regulations	<u>Materials</u>
	Information on electronic waste laws and regulations, including our products, batteries and packaging	WEEE Compliance
_	Information on product takeback and resuse program	Cisco Takeback and Reuse Program
	Sustainability Inquiries	Contact: csr_inquiries@cisco.com
Material	Product packaging weight and materials	Contact: environment@cisco.com

Warranty information

Warranty information is available on Cisco.com at the **Product Warranties** page.

Ordering information

Tables 3 and 4 give ordering information for Cisco microphones. To place an order, visit the <u>Cisco® Ordering</u> homepage. To download software, visit the <u>Cisco Software Center</u>.

Table 3. Ordering information

PRODUCT NAME	PART NUMBER
Cisco Table Microphone with 4-pin mini jack connector, 7.5 meters cable	CS-MIC-TABLE-J=
Cisco Table Microphone with 4-pin Euroblock connector, 9 meters cable	CS-MIC-TABLE-E=
Cisco Table Microphone extension cable for the 4-pin mini jack cables, 9 meters	CAB-MIC-EXT-J=
Cisco Table Microphone extension cable for the 4-pin mini Euroblock cables, 9 meters	CAB-MIC-EXT-E=
Cisco Ceiling Microphone (clips for grid ceiling mounting not included)	CTS-MIC-CLNG-G2
Cisco Ceiling Microphone optional cable (10 meter not plenum rated)	CAB-ETHRSHLD-10M
Cisco Microphone Array	CS-MIC-ARRAY-T

Table 4. Cisco microphone spare parts ordering information

PRODUCT NAME	PART NUMBER	COMPLIANCE MODEL NUMBER
Cisco Table Microphone spare cable for the 4-pin mini jack connector, 7.5mm cable	CAB-MIC-TABLE-J=	-
Cisco Table Microphone spare cable for the 4-pin Euroblock connector, 9m cable	CAB-MIC-TABLE-E=	-
Cisco Table Microphone spare table-top metal plate (3 units)	CS-MIC-TABLE-PLA=	-
Cisco Ceiling Microphone plates	CTS-MIC-CLNG-PLT=	-
Cisco Ceiling Microphone element	CTS-MIC-CLNG-ELM=	-
Cisco Ceiling Microphone dongles (RJ-45 mini jack and RJ4-5 Euroblock)	CTS-MIC-CLNG-DNG=	-
Cisco Ceiling Microphone wiring kit (2 meters/6.5 feet)	CTS-MIC-CLNG-WRK=	-
Cisco Ceiling Microphone cable (10 meters/32.8 feet)	CAB-ETHRSHLD-10M=	-
Cisco Microphone Array	CS-MIC-ARRAY-T=	TTC5-17

Note: Many of the products and features described herein remain in varying stages of development and will be offered on a when-and-if-available basis. This roadmap is subject to change at the sole discretion of Cisco, and Cisco will have no liability for delay in the delivery or failure to deliver any of the products or features set forth in this document.

Cisco Services

Cisco and our partners provide a broad portfolio of intelligent, personalized services and support that can help you realize the full value of your Cisco Collaboration investment by increasing business agility and network availability. Our portfolio of services helps you accelerate business innovation through a network-based collaboration platform that enables businesses to collaborate anywhere, at any time. For more information about these services, visit https://www.cisco.com/c/en/us/solutions/collaboration/service-listing.html.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.



For more information

Visit the <u>Cisco microphones</u> page for additional information or contact your local Cisco account representative.

Date January 2022

C78-736073-10